

12M/8M POE NVR

With AI Management Function



Face Recognition



Intrusion Detection



Line Cross Detection



Wandering Detection



People Gather Detection

5 in 1 XVR

High Resolution Preview With Excellent Compression

H.265+/H.265 5M-N/4K-N/ 5M/4K XVR



SATA



USB



RJ-45



Audio



Alarm



CVBS



RS485



BNC



NVR Series

4CH/9CH/16CH/25CH/36CH/64CH

Model NO.	NVRC430	NVRC930	NVRC1630
Video Input	9CH	9CH	16CH
Video Output	1 VGA, 1 HD	1 VGA, 1 HD	1 VGA, 1 HD
Audio Input	1 Port RCA	1 Port RCA	1 Port RCA
Audio Output	1 Port RCA(Linear, 1kΩ)	1 Port RCA(Linear, 1kΩ)	1 Port RCA(Linear, 1kΩ)
Intercom	Support (two-way)	Support (one-way)	Support (one-way)
Alarm Input	4	NO	4
Alarm Output	1	NO	4
Motion Detection	9 Channel	9 Channel	16 Channel
HD Output	1024x768/60Hz, 1280x720/60Hz, 1280x1024/60Hz, 1920x1080/60Hz, 4K(3840x2160)/30Hz		
VGA	1920x1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz		
Digital Zoom	YES		
OSD	Camera Title, Time, Recording, Motion Detection, Event Alarm		
Video Compression	H265/H264/H265+/H264+		
Resolution	4k, 5MP, 4MP, 3MP, 1080P, 960P, 720P, D1 (720×576/720×480)		
Record Rate	PAL/NTSC :4K@10x25fps,5MP@16x25fp,4MP@16x25fp,3MP@16x25fp,1080P@16x25fp, 960P@16x25fp,720P@16x25fp, D1@16x25fp		
Record Mode	Manual\Timer\Motion Detection\Smart Alarm		
Local Sync Playback	1CH 4K@30fps, 1CH 5MP@30fps,2CH 4MP@30fps, 2CH 3M@30fps, 4CH 1080P@30fps, 4CH 960P@30fps, 4CH 720P@30fps		
Decode Capability	4CH 1080P(1920x1080)@30fps		
Remote Sync Playback	YES		
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection,Event Alarm,Tag search		
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow Play, Full Screen, Frame Play ,Frame Rewind, Digital Zoom,tag,clip		
Backup Mode	USB Device/Network		
Interface	1xRJ45		
Incoming Bandwidth	80MB	80MB	100MB
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTP, p2p,PPPOE		
Onvif Version	Support Onvif 2.8		
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)		
CMS Software	Support Windows 7/ Windows 8/Windows 10/MAC OS		
Cloud Support	Yes		
Smart Phone	iPhone, iPad, Android, Android Pad		
POE	4 x Independent 100Mbps POE Network Interfaces	/	/
Interface Type	1 SATA Hard Disk Interface (3.5" SATA)		
Capacity	Up to 8TB capacity		
Language UI	Traditional Chinese, Simplified Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek, Vietnamese,Janpanese		
USB Interface	2 USB 2.0 Interfaces		
RS485	/	1port	1port
Power Supply	DC52V/1250mA	DC12V 2A	DC12V 2A
Working Environment	-10~55°C/10~90%	-10~55°C/10~90%	-10~55°C/10~90%
Dimension(W×D×H)	260*215*43(mm)	260*215*43(mm)	260*215*43(mm)

XVR Series

5-IN-1 XVR 4CH/8CH/16CH

Model NO.	XVRCT430	XVRCT830	XVRHCT430
Main Processor	MC6630	MC6630	MC6630
Video Input	4CH BNC	8CH BNC	8CH BNC
Signal Type	Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network		
Video Output	1HD,1 VGA, 1 CVBS		
Audio Input	1 Channel, RCA	2 Channel, RCA	2 Channel, RCA
Audio Output	1 Channel, RCA	1 Channel, RCA	1 Channel, RCA
Alarm Input	NO	4 CH	4 CH
Alarm Output	NO	1 CH	1 CH
Motion Detection	4CH(max 9CH in pure network mode)	8CH(max 16CH in pure network mode)	4CH(max 16CH in pure network mode)
Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications(motion detection)		
Email Alarm	Send Image to The Designated E-mail		
PTZ	Interface	RS485	
	Protocol	Pelco-D, Pelco-P	
	Baud Rate	110~921600	
	Address	0~255	
VGA/HD Output	Resolution: 1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768/60Hz		
Privacy Masking	3 Rectangular Zones (Each camera)		
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording		
Display Split	9CH / 4CH / 1CH	16CH / 9CH / 8CH / 4CH / 1CH	16CH / 9CH / 4CH / 1CH
Video Compression	H.265/H.264	H.265+/H.265/H.264+/H.264	H.265+/H.265/H.264+/H.264
Recording Resolution	5MP_Lite,4MP_Lite,3MP_Lite,1080N,720P,960H		5MP,8MP_LITE,5MP_HALF,4MP,4MP_HALF,3MP,3MP_Lite,1080P,720P,960H
Video Quality	Lowest/Low/Ordinary/Good/Better/Best		
Record Mode	Manual\Timer\Motion Detection	Manual\Timer\Motion Detection\Alarm Input\Motion and Alarm	
Decode Capability	2CH 1080P@30fps		
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection		
Playback Functions	Play, Pause, Stop, Fast play, Slow play, Rewind, Single frame forward/back, Digital Zoom, Full screen		
Backup Mode	USB Device(with fomat FAT 32)/Network/FTP		
Remote Playback	1 Channel	4 Channel / 1 Channel	4 Channel / 1 Channel
Smart Phone Playback	4 Channel	4 Channel	4 Channel
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface		
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP,DHCP, FTP, DDNS, RTP, RTSP, RTPC		
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE,HDPROVN		
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)		
CMS Software	Support Windows 7/ Windows 8/Windows 10		
Smart Phone	iPhone, ipad, Android ,Android pad		
Hard Disk Driver	1 SATA Hard Disk (2.5"/3.5" SATA, Up to 8TB)		
UTC Control	YES		
USB Interface	2 USB 2.0 Interfaces		